


FLATCABLE CONNECTORS

Low profile header – straight




RoHS compliant

DESCRIPTION

- Solder pin
- Pin length 2.9 mm alternative 4.5 mm (*) on request
- 10 to 64 positions
- Center polarization
- Space saving version
- Clip latches need to be ordered separately

PRODUCT DRAWING

PCB-hole pattern



Clip latches
Part no. 140 X 10039 X

No. of Pos.	A ± 0.2	B ± 0.1	C ± 0.1
10	19,50	17,90	4x2.54= 10.16
14	24,60	23,00	6x2.54= 15.24
16	27,20	25,60	7x2.54= 17.78
20	32,30	30,70	9x2.54= 22.86
26	39,90	38,30	12x2.54= 30.48
34	50,10	48,50	16x2.54= 40.64
40	57,80	56,20	19x2.54= 48.26
50	70,50	68,90	24x2.54= 60.96
64	89,10	86,40	31x2.54= 78.74

ORDER DATA

(Dim. = mm)

No. of Pos.	Pin length 2.9 mm	Pin length 4.5 mm*	No. of Pos.	Pin length 2.9 mm	Pin length 4.5 mm*
10	141 A 11639 X	141 A 11729 X	34	141 A 11689 X	141 A 11779 X
14	141 A 11649 X	141 A 11739 X	40	141 A 11699 X	141 A 11789 X
16	141 A 11659 X	141 A 11749 X	50	141 A 11709 X	141 A 11799 X
20	141 A 11669 X	141 A 11759 X	60	141 A 12269 X	141 A 12449 X
26	141 A 11679 X	141 A 11769 X			